

Metamark Magnetic Sheeting

Premium Grade 0.85mm

METAMARK

The Materials Company

Product Description

Metamark magnetic is designed for temporary removable signs onto vehicle panels or other sheet metal. It is a premium grade product and provides a higher than industry average magnetic pull, greater flexibility and designed to offer trouble free application and use. Unlike cheaper products it does not crack when you bend it; it is resistant to bubbling that can occur with cheaper products in wet and high temperatures; and the UV coating avoids the material from welding itself to the vehicle. The following information is generally to ensure the longevity of the signs, however failure to comply may also result in a reaction with the paintwork.

Care and Handling

- The surfaces of both the vehicle and the sign must be clean and dry. Then apply a light wax to the paint.
- It is important that magnetic signs be removed ideally every two or three days, cleaned with soapy water only (do not use solvents), dried and re positioned. In hot weather it must be done daily.
- When not in use, signs should be kept flat – preferably stored on a sheet of steel to avoid the sign gathering airborne ferrous dust.
- The panels are best designed with rounded corners to prevent corners lifting.
- All edges must be in contact with steel panels and form a snug fit.

Please Note

- The use of magnetic signs may in exceptional circumstances cause damage to vehicle paintwork.
- Do not use on body panels that have been prepared with body filler, or bridge across trim.
- Do not use on newly painted surfaces,
- Do not use on Vehicle bonnets / engine covers.
- Some type of magnets can damage sensitive equipment when brought into close proximity with it, eg: televisions.
- Only suitable for use in Northern European Climates

Magnetic sheeting

Type	Japanese Grade, Semi Anisotropic, synthetic rubber compound with strontium ferrite, and magnetised multipolar on one face.
Base Thickness	0.75mm
Pull Force	56 g/cm ²
Face Film	70 micron white gloss PVC

Overall Properties

Overall thickness	0.85mm
-------------------	--------

Durability

Shelf Life	1 year from date of purchase
Fire Rating	Self-extinguishing
External weathering	3 years – see “care and handling” above

Health and Safety

- The product does not present any undue health risk under normal conditions of use, handling and storage.
- The product has been tested and complies with the chemical analysis to detect migration according to European standard on safety of toys EN71 part 3.
- Although the product is non toxic it is advisable to consult a doctor in the unlikely event of the material being swallowed

Chemical Composition

Strontium Ferrite	85-91%
Elastomers	10%
Calcium Carbonate or Stearate	0-5%

Printing

The product is suitable for screen printing. Please refer to ink manufacturer for suitable inks.

Warranty: Metamark (UK) Limited warrants to its customers that completed decorative markings which utilise Metamark SignVinyl will remain in good condition without excessive fading or colour degradation for the specified life time of each material when correctly stored and applied in accordance with procedures outlined in the technical literature. If within the specified years of normal use Metamark SignVinyl becomes ineffective for its intended use, then Metamark will provide sufficient material to produce a new replacement marking, and will also, at its own discretion, contribute an allowance towards the costs involved in replacing the graphics. **Please Note:** The above data is given in good faith to provide an indication of the performance of the product. Purchasers should consider the suitability of each product for its intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental nor consequential loss.

Metamark (UK) Limited

- Moorfield Road Slyfield Industrial Estate Guildford GU1 1RU Tel +44 (0)1483 571111 Fax +44 (0)1483 570540
- Luneside New Quay Road Lancaster LA1 5QP Tel +44 (0)1524 387140 Fax +44 (0)1524 387147

www.metamark.co.uk
sales@metamark.co.uk