

# WIDE FORMAT LAMINATING SYSTEM

### Easymount Sign is designed to perform and built to last.

easymount.

#### **KEY FEATURES**

- Up to 5m/16ft a minute
- 25mm mounting thickness
- Variable speed control
- Integral media take-up unit
- Self gripping mandrels
- Magic eye safety feature
- Single lift mechanism
- Heavy duty construction
- Release liner take-up
- Large rollers
- Handy reverse mechanism
- Foot pedal

#### **GREAT FOR USE IN**

**IDEAL WHEN LAMINATING** 

 Single banners Reel-to-reel laminates Posters, graphics and side Mounting prints to boar • Pop-up displays Applying vinyls, tapes and adhesive films Outdoor signage and many more...

- Sign makers
- **Print finishers**

#### **Design & Performance**

Emergency stop

Magic eye safety

feature - prevents rollers from moving

when interrupted

Additional mandrel

holder

This Easymount<sup>®</sup> Sign laminator is designed to perform and built to last, with its solid heavy duty construction.

An easy-to-use laminating system with self gripping mandrels and a flip down feed tray.

The Easymount<sup>®</sup> Sign includes an integral media take-up unit, making the system ideal for single banners or reel-to-reel laminating up to 50m. The Easymount<sup>®</sup> Sign is available as a hot or cold option, in both 1.4m and 1 6m widths

**INCLUDES** 

Self gripping

mandrels

Pressure gauge

handle

Easy-to-use

control panel

Flip down feed tray

• INTEGRAL MEDIA TAKE-UP UNIT

C1 C0011

SELF GRIPPING MANDRELS

EM-S1600C

ENA C4 40011

SINGLE LIFT MECHANISM

Specifications	EM-S1400C	EM-S1600C	EM-S1400H	EM-S1600H
Laminating Speed (m/ft/min)	up to 5m/16ft	up to 5m/16ft	up to 5m/16ft	up to 5m/16ft
Max. Width (mm/inches)	1420mm/56″	1620mm/64″	1420mm/56″	1620mm/64″
Mounting Thickness (mm/inches)	25mm/1″	25mm/1″	25mm/1"	25mm/1″
Roller Diameter (mm/inches)	130mm/5″	130mm/5″	130mm/5″	130mm/5″
Laminating Temperature (°C/°F)	-	-	45°C/113°F - can be switched off	45°C/113°F - can be switched of
Pressure Adjustment	Manual	Manual	Manual	Manual
Film Core (mm/inches)	77mm/3″	77mm/3″	77mm/3″	77mm/3″
Power Supply AC (V–Hz)	220/240-50-60	220/240-50-60	220/240-50-60	220/240-50-60
Power Consumption (W)	38	38	1000	1200
Overall Dimensions (mm/inches)	1846x550x1365mm /73x22x54″	2046x550x1365mm /81x22x54″	1846x550x1365mm /73x22x54″	2046x550x1365mm /81x22x54"
Gross Machine Weight (Kg/lbs)	136Kg/300lbs	156Kg/344lbs	136Kg/300lbs	156Kg/344lbs
Gross Stand Weight (Kg/lbs)	25Kg/55lbs	30Kg/66lbs	25Kg/55lbs	30Kg/66lbs
Warranty*	1 year	1 year	1 year	1 year

\*For full terms & conditions on parts and labour warranty, visit vivid-online.com/support/warranty\_information

#### Vivid Laminating Technologies Ltd

## Vivid Laminating Technologies Ltd St Georges House, Whitwick Road, Coalville, Leicestershire LE67 3FA England

08451304050

sales@vivid-online.com

Vivid care about the environment and is an ISO 14001 registered company





Tube